






# Technical data sheet



## Proflex M

### Indoor sports flooring with surfacic area deformation

Properties	Standards	Proflex M Glued installation
<b>Sport properties</b>		
Friction	EN 13036-4	106
Shock absorption	EN 14 808	60 %
Vertical deformation	EN 14 809	2 mm
Vertical ball rebound	EN 12235	96 % (in situ)
Specular gloss	EN 13 747	17%
<b>Classification</b>		
Reaction to fire	EN 13501-1	Dfl-S1
Formaldehyde emission	EN 717-1 EN 717-2	E2
Pentachlorophenol	EN 12673	No Pentachlorophenol
<b>Technical characteristics</b>		
Abrasion	EN ISO 5470-1	0,06 g
Wear layer	EN429	3,6 mm
Resistance to indentation	EN 1516	0,07 mm
Behaviour under a rolling load	EN 1569	0,1 mm
Resistance to impact	EN 1517	No marks
<b>Specific characteristics</b>		
Surface treatment	 Highly resistant Proteco® varnish finish (non varnished available on request)	
Maintenance	 See maintenance guide	
Tree species and classification availables	 <b>Beech First</b>  <b>Oak first</b>	

#### Key points



Novi Sad – Serbie Montenegro

#### Description :

Polyethylene film  
Tarfoam 1200.

Module fixed to double battens with pins through a 10 mm thick elastomer pad, double battens grid crossed every 280 mm.

22 mm multilayer floor surface pre-assembled in a press.

#### Installation type :

Stapled

#### Destination :

Multilayer wood sport floor on a double battens module amortized.

#### Installation and maintenance guides:

Guides available on request.

#### Dimensions des lames de parquet (EN 426/EN 427):

Length: 2 520 mm  
Width : 188 mm

#### Packing:

Polyethylene film: 3 rolls x 53 ml = 159 m<sup>2</sup>  
Tarfoam 1200 foam: 25 x 2,05 ml = 51,25 m<sup>2</sup> (73,4 kg)  
Battens : 2240 x 60 x 20,5 mm = 180 m<sup>2</sup>/palette  
Boards : Packs of 6 laminas (2,84 m<sup>2</sup>)

#### Total thickness (EN 428):

88 mm (± 2 mm)

#### Total weight (EN 430) :

20 kg (± 100 g)



#### COMPATIBLE SLABS:

Concrete, hot-applied asphalt and asphalt screed, anhydrite screed.

Any deviation of the slab must be corrected prior installation (3 mm under a 2 m straight edge). See installation guide.

	<b>EN 14904 : 2006</b> Revêtement de sol sportif intérieur à base de parquet contrecollé sur sous construction bois et mousse.	Fieldturf Tarkett SAS 2 rue de l'Egalité 92748 NANTERRE CEDEX FRANCE
	   	EN 13489 Proflex M

FIELDTURF TARKETT SAS  
2, rue de l'Egalité,  
92748 Nanterre Cedex France  
Tél. 33 (0)1 41 20 40 40  
Fax. 33 (0)1 41 20 47 18/19  
<http://www.fieldturfarkett.com>

