

INSTALLATION AND MAINTENANCE INSTRUCTIONS

COMMERCIAL HOMOGENEOUS TILE

Added Dimensions

I. INSTALLATION

The sub-floor must be flat, sound, dry, solid, hard smooth, clean and moderately absorbent.

Store the cartons in the area to be installed 48 hours prior to installation.

The moisture transmission rate of concrete surfaces must be below 5 lbs with Tarkett 800 Adhesive.

7 to 10 lbs with Tarkett Spray SMART systems

Plywood subfloors must have a minimum rating of CC underlayment grade.

Minimum room temperature : +65 ° F.

Minimum subfloor temperature : + 65° F.

Use the same run number for each large area and install by sequential pallet numbers.

Recommended adhesives:

Tarkett 800 Pressure Sensitive applied with recommended notch trowel / Allow adhesive to fully set.

Tarkett Spray SMART 120 Gold 7-11

Tarkett Spray SMART 120 Platinum 10-12

Laying With Grout Fit: Lay tile in one direction following back printed directional arrows and grout width / alignment.

Laying Without Grout Fit: (With texture) Lay tile alternating direction observing back printed directional arrows.

USE : Wait 24 hours before trafficking and 48 hours before moving furniture.

II. CLEANING

NOTE: Textured floor tile should be maintained with Bristle brushes for cleaning & Hogs Hair pads for buffing. An occasional brush scrubbing of grout will help prevent debris build up.

First use :

Sweep with a soft brush and then scrub surface with a neutral floor cleaner to remove construction debris.

Rinse with clean water.

Textured Products: Apply two coats of a quality acrylic emulsion floor finish.

Smooth Products: Dry buff floor with medium to low speed buffer > 1,800 RPM

Daily cleaning :

Sweep then mop with a small amount of neutral detergent diluted in clean warm water.

Periodical cleaning :

Deep scrub areas as needed followed by appropriate surface finishing procedure.

Textured Products: Spray buff as needed using Hogs Hair pads.

Smooth Products: Dry buff floor with medium to low speed buffer > 1,800 RPM

When using floor finish, stripping and recoating of the floor should be done once or twice a year.

Warning :

Rubber-based caps or rollers may lead to permanent marks : replace them with plastic caps or attach protective felt. Also put protective felt under the legs of wooden furniture.

An efficient walk off matting system is recommended at all exterior entrances.