



800-558-2240 (Samples)  
800-366-2689 ext. 2706 (Tarkett Commercial Technical Assistance)  
FAX: 713-869-5271 (Tarkett Commercial Technical Assistance)

Technical Assistance E Mail: [AzTech@Tarkett.com](mailto:AzTech@Tarkett.com)

## SECTION 09.65.19.00 – COMMERCIAL HOMOGENEOUS TILE

- A. Type: Azrock/Commercial Homogeneous Tile, ASTM F 1700 Solid Vinyl Floor Tile; 1/8 inch gauge; minimum 0.45 CRF per ASTM E 648; maximum smoke density of 450 per ASTM E 662; static load limit of 800 psi or higher; minimum slip resistance rating of > 0.60, Quality Assurance, latest ISO 9000 Standard.
1. Solid Vinyl Tile Manufacturer: Azrock, a brand of Tarkett Commercial Flooring, Telephone 800-558-2240 (samples) and 800-366-2689 ext. 2706 (Azrock Technical Assistance); Fax 713-869-5271 (Azrock Technical Assistance). E-mail Technical Assistance: [AzTech@Tarkett.com](mailto:AzTech@Tarkett.com)
  2. Color:
    - a. Milano, 16 inch by 16 inch (12 colors).
    - b. Milano SR, 16 inch by 16 inch (5 colors), slip resistance rating of 0.8.
    - c. Cortina Grande, 16 inch by 16 inch (26 colors).
    - d. Cortina Grande SR, 16 inch by 16 inch (7 colors), slip resistance rating of 0.8.
    - e. SolidAire, 16 inch by 16 inch (20 colors).
    - f. Karim Kolors, 16 inch by 16 inch (10 colors).

**Specifier Note:** All products are available by special order, minimum 300 carton run, with special size, shape, surface and edge affects. Select and incorporate from the following choices available:

d. Added Dimensions (Options)

Size: 16 inch by 16 inch, (12 inch by 12 inch)

Shape: "Node", "Wave", "Triangle", "Honeycomb"

Grout: 1/8 inch- 2 sided Grout-Fit

Textures: Rustic Stone, (Slate)